




# ISO<sup>°C</sup>LIGHT

STANDARD CONFIGURATION\*



## Rear doors

Two double-walled barn doors, revolving 270°, including aluminium door retainers, aluminium hinges and an internal espagnolette locking system out of stainless steel

## Tail lift DHOLLANDIA

Top flap, mounted above a Dholandia DH-LMA tail lift, equipped with rubber sealing joints, gas springs and aluminium hinges.



Fully insulated 25 mm thick sandwich roof, reinforced with aluminium tubes. As a standard the roof is equipped with an LED ceiling light with an integrated PIR movement detector.

Sandwich wall panels with a wall thickness of 25 mm. Both on the in- and the outside covered with a polyester sheet and a core of insulating PUR-foam. A surrounding 250 mm high synthetic kickboard is mounted at the underside.



Aluminium subframe for plug-and-play mounting to the chassis, adapted to the chassis, consisting out of longitudinal and cross beams. On top is a 15 mm thick waterproof glued loading floor from Scandinavian plywood out of one piece, with an anti slip top layer. Watertight finish all around.

## FOR ALL LIGHT CONDITIONED TRANSPORT

For fresh and conditioned transport the cityBOX ISO-Light is exactly what you need. This lightweight insulated box body meets all your light refrigerated transport needs. The sandwich walls are provided with an insulating core of PUR foam. With the help of the right cooling engine a constant temperature up to +7° C. can be maintained. Due to the seamless and smooth exterior walls the ECO-Light is highly suitable for applying decals.



Wall thickness: 25 mm  
Wall colour: B4B4 Candy White  
DB9147 Arctic White  
CTS01 Cream White

## Dimensions ISO-light:

Internal length + 100 mm = External length  
Internal width + 55 mm = External width  
Internal height - 35 mm = Passage height

## Fully equipped as a standard:

- ✓ Mud guards
- ✓ Mud flaps
- ✓ Lateral cyclist protection
- ✓ Side marker lights
- ✓ 3<sup>rd</sup> braking lights
- ✓ Top marker lights

## Standard dimensions:

External width 2.220 mm  
Internal height 2.200 mm

\*This product sheet describes a standard basic configuration. Ask us or your local dealer about the wide range of options available.



The cityBOX is available in many different configurations and fits to any vehicle make and model!